

Calibration of the PHENIX Lead Scintillator Calorimeter

H.Torii for the PHENIX
Collaboration

Kyoto Univ./RIKEN

Contents

- Lead Scintillator Calorimeter(PbSc)
- Test beam results
- Calibration in PHENIX configuration
- Summary

L. Aphecetche, T. Awes, S. Bathe, H. Baumschling, A. Bazilevsky, S. Belikov,
S. Botelho, S. Chernichenko, D. Bucher, H. Buesching, G. David,
A. Denisov, D. d'Enterria, H. Delagrange, A. Durum, R. Glasow, Y. Goto,
M. Grosse-Perdekamp, S. Fokin, H. Hamagaki, K. Imai, M. Ippolitov,
E. Kistenev, S. Kametani, V. Kochetkov, V. Manko, G. Martinez,
T. Matsumoto, Y. Melnikov, S. Mioduszewski, S. Nikolaev, A. Nyanin,
V. Onuchin, K. Oyama, Y. Schutz, A. Soldatov, T. Peitzmann, K. Reygers,
T. Sakaguchi, R. Santo, S. Stall, P. Stankus, T. Thomas, H. Torii, A. Usachev,
A. Vinogradov, M. Volkov, S. White, C. Woody, G. Young
for the PHENIX Collaboration

Special thanks for pictures

: E.Kistenev, G.David, A.Bazilevsky

Lead Scintillator Calorimeter(PbSc)

Shashlik type calorimeter

Scintillator plates 55.2x55.2x1.5mm

Lead plates 110.4x110.4x4mm

Shish-kebab geometry wave shifter fiber readout


6x6 fibers $\rightarrow$ 1 PMT = 1 tower

2 x 2 towers = 1 module

6 x 6 module = 1 super module

6 x 3 super module = 1 sector

	PbSc
Size(cm x cm)	5.52 x 5.52
Depth(cm)	37.5
Number of towers	15552
Sampling fraction	$\sim 20\%$
η cov.	0.7
ϕ cov.	90+45deg
η/mod	0.011
ϕ/mod	0.011
X_0	18
Molière Radius	$\sim 3\text{cm}$






Very fine segmentation

Energy linearity and resolution

Energy resolution
 $2.1\% \oplus 8.1\% / \sqrt{E(\text{GeV})}$

nucl-ex/0202009





Energy leakage

Light attenuation in the WLS fibers
 (effective $L_{\text{att}} \sim 100\text{cm}$)

Timing and Position resolution

nucl-ex/0202009


- Timing resolution




Position resolution

Hadron response


- We measured hadron energy response at test beam
 - 0.3-2GeV/c π, K, p
 - 40GeV/c π^+
- Two structure
 - Ionization
 - 270MeV for 1GeV/c π
 - Hadronic shower
 - Distribution from the ionization energy to its kinematics energy.
- The measured energy of electromagnetic shower is well separated from that of hadronic shower.



PHENIX Configuration



- 2 Arm $\times$ 4 sectors
 - Lead Scintillator(PbSc)
 - 6 sectors(15552 channels)
 - Lead Glass (PbGl)
 - 2sectors (9216 channels)
- $\sim 5\text{m}$ distance from collision point
- $|\eta| < 0.38$ $\phi = 180^\circ$






Energy Calibration Strategy in PHENIX configuration

- Before installing into PHENIX configuration, all towers are calibrated using cosmic muon traversing laterally.(1998??)
- The calibration parameters are transported into PHENIX configuration by laser monitoring system.
 - The procedure is well established through several beam test
- Remained misalignment is corrected using charged particle from collision traversing lengthwise
- The absolute energy scale is obtained by physics signal
 - π^0 mass
 - E/p
 - Ionization energy


Energy calibration

- All towers calibrated by ionization energy of cosmic muon traversing laterally
 - 42MeV
- Additional misalignment is calibrated by charged π traversing lengthwise
 - 270MeV



Laser monitoring system

- UV laser (YAG laser) is used for calibration and monitoring system
 - The light intensity is monitored with PIN diodes at each intermediate splitter that are used for normalization.
 - Light is injected into each module through a “leaky fiber” to simulates an electromagnetic shower
- Laser monitoring system works for
 - Transportation from cosmic muon calibration into PHENIX configuration
 - Trace of time drift




Absolute energy calibration

Three independent measurement results in


2%

accuracy of absolute energy calibration


Ionization energy



π^0 mass



electron E/p





Timing calibration

Before correction

- Strategy
 - Slewing correction is obtained by laser and photon.
 - Time zero is adjusted using photon sample purified by shower shape cut.
- Timing measurement is very important in heavy ion collision
 - to reduce slow hadron contribution

Currently, time resolution is
 $\sim 400\text{psec}$ for $0.5\text{GeV } \gamma$
work in progress





*After correction
+ photon PID*

Hadron PID

- Timing measurement is also important for hadron physics
 - For run1, π -K separation up to 0.8 GeV/c


0.7-0.8 GeV/c



π^0 measurement

Run1 Au+Au $\sqrt{s_{NN}}=130\text{GeV}$


10% Central events



Run2 p+p $\sqrt{s_{NN}}=200\text{GeV}$

$m(\pi^0) = 135.1\text{ MeV}/c^2$
 $\sigma_m(\pi^0) = 10.3\text{ MeV}/c^2$

$m(\eta) = 547\text{ MeV}/c^2$
 $\sigma_m(\eta) = 34\text{ MeV}/c^2$



Pi0 measurement is successful from p+p to Au+Au collision

Summary

- Test beam results
 - Energy linearity and resolution($2.1\% \oplus 8.1\%/\sqrt{E}$)
 - Timing resolution, Position resolution($1.4\text{mm} + 5.9\text{mm}/\sqrt{E}$), Hadron rejection
- PHENIX configuration
 - The relative energy for all towers is calibrated using the ionization energy of a cosmic muon traversing laterally and that of a charged pi traversing lengthwise
 - Gain drift during run is corrected by laser monitoring system.
 - The absolute energy scale is 2% accuracy from
 - E/p
 - π^0 mass
 - Ionization energy
 - Time measurement
 - Hadron PID shows π/K separation up to $0.8\text{GeV}/c$ in Run1